

## BOGE S-4 series

Designed to take the lead



### TECHNICAL DATA

BOGE type	Max. pressure bar	Effective free air delivery m <sup>3</sup> /min	Rated output		Dimensions B x T x H (mm)	Compressed-air outlet	Weight with sound insulation kg	Weight with super sound insulation kg
			Main-drive kW	Fan-motor kW				
S 46-4 LF	7.5	2.37 - 8.38	45	2.2	2100 x 1200 x 1720	DN 65	1770	1810
S 46-4 LF	10	2.44 - 7.20	45	2.2	2100 x 1200 x 1720	DN 65	1770	1810
S 46-4 LF	13	3.33 - 5.85	45	2.2	2100 x 1200 x 1720	DN 65	1770	1810
S 55-4 LF	7.5	2.37 - 10.69	55	2.2	2100 x 1200 x 1720	DN 65	1770	1810
S 55-4 LF	10	2.44 - 8.70	55	2.2	2100 x 1200 x 1720	DN 65	1770	1810
S 55-4 LF	13	3.33 - 7.06	55	2.2	2100 x 1200 x 1720	DN 65	1770	1810
S 55-4 L	7.5	9.81	55	2.2	2100 x 1200 x 1720	DN 65	2030	2070
S 75-4 LF	7.5	2.37 - 13.54	75	2.2	2100 x 1200 x 1720	DN 65	1770	1810
S 75-4 LF	10	2.84 - 11.61	75	2.2	2100 x 1200 x 1720	DN 65	1770	1810
S 75-4 LF	13	3.33 - 9.50	75	2.2	2100 x 1200 x 1720	DN 65	1770	1810
S 75-4 L	10	9.52	75	2.2	2100 x 1200 x 1720	DN 65	2140	2180